



COLORSOFT CWS LIQUID

Product Information

Colorsoft CWS liquid is a specially developed softener for cotton, polyester, wool and their blends. It imparts soft and limpy handle to the treated substrate. It does not impair the whiteness or brightness of garments. Colorsoft CWS liquid can be applied by pad as well as by exhaust application. Thus, it is suitable to finish the material in any form such as yarn knits, wovens or even garments.

FEATURES

- Non-yellowing
- Universal softener

BENEFITS

- Suitable for finishing of whites & pale shades
- Single product for finishing cotton, polyester, wool and their blends and garments

PROPERTIES

Appearance ------ \rightarrow White to creamish liquid.

Ph 1% -----→5+/-2.

Ionic nature-----→Cationic.

Miscibility ----- \rightarrow Miscible with water.

Compatibility----- \rightarrow Compatible with cationic and nonionic.

Stability ------ \rightarrow Stable to dilute and dilute alkalies.

DOSAGE & APPLICATIONS

Padding Process:

20-30g/l	Colorsoft CWS liquid	1
20 2081		~

65-75% Pick-up

рН 5.0-6.0

Temp. 130-160 deg

Exhaust method:

2-3%	Colorsoft CWS liquid
pН	5.0-6.0
Temp.	30-40 deg
Time	20-30 min.

CAUTION

- In case of skin contact, wash with plenty of water.
- In case of eye contact, wash with plenty of water and seek medical advice.

PACKING MATERIAL

50KG BAG PACKING.

The storage guidelines for the product

1.Storage Conditions:

- Store the product in its original container.
- Keep it in a dry, dust-free location at temperatures below 50°C.

2.Ventilation and Compatibility:

- Ensure the storage area is well-ventilated.
- Keep the product away from incompatible materials (as specified in the Material Safety Data Sheet) and food items.

3.Container Handling:

- Seal the container tightly after each use.
- Avoid pouring unused material back into the container.

4.Shelf Life:

• The product remains usable for at least 24 months from the date of manufacture.

WORK

Email: kavin@coloriq.org

Ph no: +91-9500325253

No.72, SKC Road, opposite to Rubeen bags, Erode-638001.

